


Instruction Manual



GTA

Drag Type Offset Disc Harrow - Heavy Duty

BALDAN

INTRODUCTION

We thank you for the preference and congratulate your excellent choice in acquiring an implement of outstanding quality, manufactured in accordance with the advanced technology of **BALDAN IMPLEMENTOS AGRÍCOLAS S/A**.

This manual will assist you, in proceeds necessities, since when you bought until the operational proceeds application, security and maintenance.


The **BALDAN** guarantees that deliver this implement to the dealer, working properly, and in perfect conditions.

The dealers it's under the responsibility to keep the protection and conservation while keep the implement in your stock, and than, to assembly, tighten, lubrication and overhaul.

On time of the technical deliver, the dealer must to have conducted the user customer about the manutentation, safety, and your obligations in a possible technical assistance, the obligation to see the warranty terms and read the instruction manual. Any solicitation of warranty, please contact our Baldan technical service, by your Baldan dealer that you bought our implement. Reaffirm the necessity to read carefully of warranty certificate and note all of items from this manual, therefore you will increase the working life of your equipment.



Instruction Manual



GTA

Drag Type Offset Disc Harrow - Heavy Duty

BALDAN IMPLEMENTOS AGRÍCOLAS S/A.
CNPJ: 52.311.347/0009-06
Insc. Est.: 441.016.953.110



Scan the QR Code on the identification plate of your device and access this Instruction Manual online.

BALDAN

INDEX

01. Safety standards	4
02. Components	9
03. Technical specifications	10
04. Assembly	11
<i>Union of rear and front frames</i>	13
<i>Assembling the hydraulic piston (optional)</i>	14
<i>Assembling the coupling header</i>	15
05. Coupling the disc harrow to the tractor drawbar	16
06. Adjustments and operations.....	17
<i>Adjusting the disc harrow opening</i>	17
<i>Side displacement of the disc harrow</i>	17
<i>Adjusting the cross bar on the front frame</i>	18
07. Operations	19
08. Lubrication	20
<i>Table greases and equivalents</i>	20
09. Lubrication points	21
<i>Adjustment of bearings</i>	23
10. Cleaning.....	23
11. Approximate production	24
12. Table of approximate production	25
13. Identification	26
14. Notes.....	28

01. SAFETY STANDARDS



THIS SYMBOL INDICATES IMPORTANT SAFETY WARNING. WHENEVER YOU FIND IT IN THIS HANDBOOK, CAREFULLY READ THE MESSAGE THAT FOLLOWS AND BE AWARE OF THE POSSIBILITY OF PERSONAL INJURY.



WARNING

- *Read this instruction manual carefully to know the recommended safety rules.*



WARNING

- *Only start the tractor operations, when are you properly accommodated and with the seat belt fastened.*




WARNING

- *Never carry people over the tractor or equipment.*



WARNING

- *There are risks of serious injury by tipping when working on slopes.*
- *Never use excessive speed.*



01. SAFETY STANDARDS



WARNING

• Do not work with the tractor if the front bee without enough weight to the rear equipment. There is tendency to lift, add weights at front or front wheels.




WARNING

• Before any equipment maintenance, make sure that is properly stopped
• Avoid getting hit




WARNING

• Remove the ignition key before performing any type of maintenance in GTA. Protect yourself against possible injuries or death caused by GTA unexpected start-up.
• Do not start the tractor up if GTA is not properly engaged.



WARNING

• Do not perform adjustments while GTA is running.
• When performing any service on GTA, switch off the tractor first. Use appropriate tools.



THE SAFETY ALERT SYMBOL IDENTIFIES IMPORTANT MESSAGE ON THE MESSAGE ON THE ENGINE, WHEN YOU SEE THIS SYMBOL, BE ALERT TO THE POSSIBILITY OF DEATH OR PERSONAL INJURY. FOLLOW THE INSTRUCTIONS IN THE SAFETY MESSAGE.

01. SAFETY STANDARDS

WARNING

- Before beginning the work or transportation of GTA, check if there are people or blockages close to it.



WARNING

- Always maintain places of access and work free of residues such as oil or grease to prevent accidents.



WARNING

- Keep away from the active seeder elements (discs), they are sharp and can cause accidents.
- Whenever performing any work on the discs, wear safety gloves on your hands.



WARNING

- Dispose residues inappropriately affects the environment and the ecology since you will be polluting rivers, canals or the soil.
- Inform yourself about the proper way of recycling or disposing residues.









PROTECT THE ENVIRONMENT!











ALCOHOLIC BEVERAGE OR SOME MEDICATIONS MAY CAUSE LOSS OF REFLEXES AND CHANGE THE OPERATOR'S PHYSICAL CONDITIONS. FOR THIS REASON, NEVER OPERATE THIS EQUIPMENT UNDER ANY OF THESE SUBSTANCES.



THE MISMANAGEMENT OF THIS EQUIPMENT CAN RESULT IN SERIOUS OR FATAL ACCIDENTS. BEFORE PLACING THE EQUIPMENT IN OPERATION, CAREFULLY READ THE INSTRUCTIONS IN THIS HANDBOOK. MAKE SURE THAT THE PERSON RESPONSIBLE FOR THE OPERATION IS INSTRUCTED ON THE PROPER AND SAFE HANDLING, IF HE HAS READ AND UNDERSTOOD THE HANDBOOK OF THIS PRODUCT.

- 01-  When operating the equipment, do not allow people to stay very close or on it.
- 02-  In making any assembling and disassembling service in the discs, always use safety gloves.
- 03-  Before connecting or Disconnecting hydraulic hoses, relieve the system pressure by moving the command with the tractor off.
- 04-  Periodically check the conservation status of the hoses. If there is evidence of leaks, immediately replace them because the oil works under high pressure and can cause serious injury.
- 05-  Do not wear loose clothing as they can become entangled in moving parts.
- 06-  When turning the tractor engine on, be properly seated on the operator's seat and aware of the correct and safe management of both tractor and implement. Always put the selector lever in neutral, turn off the power take-off command and place the hydraulic commands in the neutral position.
- 07-  Do not run the engine in indoor environments without adequate ventilation, as the exhaust fumes are harmful to health.
- 08-  When maneuvering the tractor to the implement hitch, make sure that there is plenty of room and that there is nobody very close, always do the maneuvers in low gear and be prepared to brake in emergency situations.


- 09-  Do not make adjustments with the implement in operation.
- 10-  When working on slopes, proceed with caution when trying to maintain the necessary stability. In case of unbalance, reduce the throttle and turn the wheels of the tractor to the side of the slope.
- 11-  Always drive the tractor at speeds compatible with safety, especially when working on uneven ground or slopes. Keep the tractor always engaged.
- 12-  When driving on roads, keep the tractor brake pedals interconnected and use safety signs.
- 13-  Do not operate the tractor if the front is light. If there is a tendency to rise, add weights on the front or front wheels.
- 14-  Leaving the tractor, put the shifter in neutral and apply the parking brake.
- 15-  Alcoholic beverages and some medications can cause loss of reflexes and change the physical conditions of the operator. Therefore, never operate this equipment, under the influence of these substances.
- 16-  Read or explain all the procedures above to the operator who cannot read.

GTA - DRAG TYPE OFFSET DISC HARROW - HEAVY DUTY

Figure 1

02. COMPONENTS

- 01 - Front Frame
- 02 - Rear Frame
- 03 - Front stabilizer bar
- 04 - Rear stabilizer bar
- 05 - Lock handle
- 06 - Lock ruler
- 07 - Coupling header
- 08 - Discs
- 09 - Disc wiper
- 10 - Hose support



03. TECHNICAL SPECIFICATIONS

Table 1

Model	No. of Discs	Disc spacing (mm)	Disc diameter (ø)	Spherical Discs (mm)	Axle diameter (ø)	Working width (mm)	Working depth (mm)	Approx. weight (Kg)			Required tractor power (HP)
								30"	32"	34"	
GTA	10	340	30" - 32" - 34"	7,5 - 9,0 - 12,0	2.1/4"	1530	200 - 300	1655	1705	1770	90 - 100
GTA	12	340	30" - 32" - 34"	7,5 - 9,0 - 12,0	2.1/4"	1870	200 - 300	1835	1895	1966	108 - 120
GTA	14	340	30" - 32" - 34"	7,5 - 9,0 - 12,0	2.1/4"	2390	200 - 300	2007	2076	2157	126 - 140
GTA	16	340	30" - 32" - 34"	7,5 - 9,0 - 12,0	2.1/4"	2550	200 - 300	2253	2332	2431	144 - 160
GTA	18	340	30" - 32" - 34"	7,5 - 9,0 - 12,0	2.1/4"	2890	200 - 300	2547	2635	2754	162 - 180
GTA	20	340	30" - 32" - 34"	7,5 - 9,0 - 12,0	2.1/4"	3230	200 - 300	2753	2851	2978	180 - 200

BALDAN reservase el derecho de cambiar las características técnicas de este producto sin previo aviso.
Las especificaciones técnicas son aproximadas y informadas en condiciones normales de trabajo.

04. ASSEMBLY

- 01 - Check the parts with the parts list that is inside the packing box.
- 02 - The assembly must always begin with the set of discs.
- 03 - Place the shaft Item 1, Figure 2, the concave thrust washer Item 2, one washer Item 3, a nut item 4, the latch item 5 and fix with the screw Item 6 as shown in figure 2. Note that the nut is facing with the tip of the shaft.
- 04 - Place the shaft item 1, the first disc item 7, one bearing * Item 8, another disc Item 7, the separator reel item 9 and so on, as figure 2.
- 05 - When the set is complete with all discs, bearings and separator reels, place the convex thrust washer item 10, the washer Item 3, another nut Item 4, giving a prior tightening to firm the set. Check if the washers and discs did not come out of the socket.
- 06 - Then, wedge the set of discs and tighten the nut Item 4 through impacts. When it is about achieving maximum grip, adjust the lock Item 5 with the convex washer, always tighten the nut to match the drilling, fasten them through the screw Item 6.
- 07 - View of the front and rear item assembled with the lubrication system to the rear part of the implement to provide greater protection.
- 08 - When in oil bath, roller bearings should be assembled with the lubrication system (plug) facing the back of the implement according to figure 3.




Figure 2




ATTENTION

Before beginning assembly, place PROTECTIVE GLOVES on hands.



01 - Figure 3 shows the assembly of the disc items for each disc harrow model and its respective frames.

Figures 3



02 - When assembling the frame on the disc item, note that the bracket to fix the bearings (Shoe) should face the concavity of discs, as shown in figure 4.




Figure 4

LEGEND

- = BEARING
- = SEPARATOR REEL
- ⌒ = DISC

- 01 - Couple the front frame Item 1, Figure 6, to the rear frame item 2 through the coupling shaft item 3 with flat washer, nut and lock screw. Couple the rear stabilizer bar item 4 on the rear frame item 2, with the coupling shaft Item 5 and washer, nut and lock pin item 7.
- 02 - Attach the rear stabilizer bar item 5 with front stabilizer bar item 7 through the coupling shaft item 8, coupling it to the front frame item 1, with the pin Item 10.
- 03 - Place the lock handle item 11 on the front stabilizer bar, passing the adjustment latch item 12 through inside the lock handle, coupling the rear stabilizer bar through screw item 13.








Figure 5

ASSEMBLING THE HYDRAULIC PISTON (OPTIONAL)

- 01 - Set the piston Item 1 Figure 6, so that the base of the cylinder is placed on the front frame item 2, through the pin item 3, locking it with the screw and the piston rod attached to the rear frame item 4, through pin item 5 locking with screw Item 6.
- 02 - Connect the hoses Item 7 in the hydraulic piston.
- 03 - Place the front and rear frames on flat and clean place.
- 04 - Lift a frame (front or rear), assemble the disc set online, observe the their arrangement in Figure 3. Make it coincide with the drilling of shoes with those of bearing, and make the assembly through screws Item 1 Figure 7, noting that the bracket support (shoe) should be facing the concavity of the disc as shown in Figure 3.
- 05 - Lift the other part of the disc harrow and repeat the above operation, verifying that the concavity of the discs of one section should be unlike another.
- 06 - Fix the wipers item 1, figure 8, on supports.
- 07 - Place the central wipers item 2 figure 8 in the front and rear frames.



- 01 - Place the complete crossbar item 1 Figure 9, in the front frame item 2 using the screws Item 3.
- 02 - Place the coupling header item 4, between the upper and lower plates of the cross bar, fixing it with the screw item 5, washer and nut item 6. Place the adjustment pin item 6.
- 03 - Fix the hose support Item 8 in the header, passing the hoses through it.



05. COUPLING THE DISC HARROW TO THE TRACTOR DRAWBAR

- 01 - To couple the disc harrow to the tractor drawbar, their alignment should be observed, adjust the exact height of the disc harrow and use the coupling pin "L" item 1 Figure 10.
- 02 - Before connecting or disconnecting hydraulic hoses, stop the engine and relieve the system pressure, activating the command levers completely. Make sure that, by relieving the system pressure, no one gets hurt with the movement of the equipment.



ATTENTION

When coupling the implement, find a safe and easily accessible place, always use low gear with low throttle.



ATTENTION

Connect the hoses item 2 on the quick hitch of the tractor.



NOTE

If the tractor is not equipped with hydraulic control and output for remote control, Baldan will optionally provide remote control kit appropriate for each tractor model.




Figure 10

06. ADJUSTMENTS AND OPERATIONS

ADJUSTING THE DISC HARROW OPENING

- 01 - To obtain optimum penetration of discs, the disc harrow opening varies according to the type of soil.
- 02 - In soils more difficult to penetrate, increase the opening "A" of the disc harrow, according to figure 12.
- 03 - In loose and lighter soils, you should reduce the disc harrow opening
- 04 - To open or close, pull the rope that goes up the tractor driver, releasing the opening adjustment set. If you want to open the disc harrow, move the tractor forward, if you want to close the disc harrow, move the tractor backward.
- 05 - For transportation, completely close the disc harrow.

SIDE DISPLACEMENT OF THE DISC HARROW

- 01 - This side displacement should be done when the disc harrow is not giving a perfect finishing, that is, leaving tractor trail. The disc harrow should work centralized with the tractor traction line. To do this, move the upper and lower header plates to the right or to the left, as shown in figure 12.
- 02 - The coupling header operates in the center hole of the top and bottom plates for intermediate soils; displacing the other holes, changes the angle of the front section, as in Figure 12

- 1 *Increases penetration*
- 2 *Levels the coupling header*
- 3 *Decreases penetration*





Figure 11

ADJUSTING THE CROSS BAR ON THE FRONT FRAME

01 - The coupling arms are welded in the front frame, which has three holes as in Figure 11, whose main purpose is to level the header of the disc harrow in relation to the tractor drawbar.

Figure 12



NOTE

Increasing the angle A greater penetration. Decreasing the angle A, lower penetration.



NOTE

When engaged in the upper hole, penetration will be greater and therefore in the lower hole, penetration will be lower.

07. OPERATIONS

- 01 - Before starting operations with the disc harrow, revise it completely, retighten all bolts, nuts, hose terminals, axes and especially disc sections.

HOW TO START HARROWING

- 01 - To start harrowing, you should follow the terraces or contour lines, starting operation so that the terrace is on the left side of the tractor driver.
- 02 - Do not turn it to the right, see figure 18. The harrowed soil must always be at the left side of the tractor driver.
- 03 - The figure below shows some operation systems.

TO HARROW TOWARDS THE OUTSIDE





Figure 11


TO HARROW TOWARDS THE INSIDE

- 01 - In this way, we obtain greater perfection. When you start working in the headboards, you should start another plot.



PLOTS WITH CONTOUR LINES

- 01 - In soils with contour lines, it is usual to start two plots at a time, having the care to start working with the contour line of the left side of the tractor driver. When you reach the middle of the contour line, you should start another plot to save fuel.



08. LUBRICATION

- 01 - Lubrication is essential for optimal performance and durability of moving parts of your disc harrow.
- 02 - Before start working, carefully lubricate all grease fittings, always observing re-lubrication intervals, making sure about the quality of the lubricant, as its efficiency and purity, avoiding the use products contaminated by water, dirt, etc.

LUBRICATION OF ROLLER BEARINGS IN GREASE

- 01 - Clean the grease fitting with a clean and lint-free cloth and replace damaged ones.
- 02 - The amount of grease in each bearing is 500 grams.
- 03 - The roller bearings should be re-lubricated every 12 hours, using the grease specified in the table below.
- 04 - The oil change should be done every 1200 working hours. Use SAE 90.mineral oil

LUBRICATION OF ROLLER BEARINGS IN OIL BATH

- 01 - In the first days of working with the disc harrow, check the oil level of bearing daily and the seals.
- 02 - Check the oil level every 120 hours.
- 03 - The oil change should be done every 1200 working hours. Use SAE 90 mineral oil.

TABLE GREASES AND EQUIVALENTS

Manufacturer	Type of grease recommended
Petrobrás	Lubrax GMA 2
Atlantic	Litholine MP 2
Ipiranga	Super Grasa Ipiranga Ipiranga Super Grasa 2 Ipiflex 2
Castrol	LM 2
Mobil	Mobilgrease MP 77
Texaco	Marfak 2 Agrotex 2
Shell	Retinax A Alvania EP 2
Esso	Multipurpose grease H
Bardahl	Maxlub APG 2 EP

Table 2




If there are manufacturers and /or equivalent brands which are not listed in the table, refer to the manufacturer's technical manual.

09. LUBRICATION POINTS

Table 3

Item	Part Description	Number of nipples						Oil replacement	Lubricate with grease	Retighten	Replace	Check	Maintenance intervals
		GTA 10 Discs	GTA 12 Discs	GTA 14 Discs	GTA 16 Discs	GTA 18 Discs	GTA 20 Discs						
1	Bearings	4	4	6	6	8	8		X				12 hours
2	Union of frames	1	1	1	1	1	1		X				
3	Piston rod	1	1	1	1	1	1		X				
4	Union of stabilizer bars	1	1	1	1	1	1		X				60 hours
5	Rear stabilizing bar	1	1	1	1	1	1		X				
6	Piston coupling	1	1	1	1	1	1		X				
7	Front stabilizing bar	1	1	1	1	1	1		X				
8	Coupling shackle	1	1	1	1	1	1		X				
9	Hydraulic system											X	
10	Bearing oil											X	120 hours
11	Nuts, screws and shafts									X			
12	Bearings							X					1200 hours
13	Seals										X		1500 hours
14	Bearings										X		
15	Discs										X		Whenever required



ATTENTION

After the first day of work with the implement, tighten all screws and nuts.

Figure 14

- 01 -When bearings show clearances, adjust them as follows:
- 02 -Loosen the nut Item 1 Figure 15, remove the lock item 2, and adjust the bearings by tightening the cover item 3, taking into account that the bearing should not work too tight not to wear excessively the bearings.
- 03 -Replace the lock item 2, the nut item 1 and retighten it.

10. CLEANING

- 01 -When the disc harrow remains inactive for an extended period, make a general cleaning, make sure the cover is not worn out. If so, apply a general coat, protective oil and lubricate the disc harrow completely. Check the discs, apply a coat of paint on them and protective oil




Figure 15

11. APPROXIMATE PRODUCCION

01 -To calculate the approximate hourly production of the disc harrow, use the following formula:

$$A = \frac{L \times V \times F}{X}$$

WHERE

- A = Area to be worked
- L = Working width of the disc harrow (in meters)
- V = Average tractor speed (meters / hour)
- F = Production factor - 0.90
- X = Hectare value - 10,000 m²

• **Example:** Using a 14-disc disc harrow, how many Hectare it will produce in an hour of work at an average speed of 7km / h?

- A = ?
- L = 2.39m
- V = 7.000m/h
- F = 0.90
- X = 10.000 m²

$$\frac{A = 2,39 \times 7.000 \times 0,90}{10.000} = 1,50 \text{ Ha/h}$$

12. TABLE OF APPROXIMATE PRODUCTION

Table 4

Model	Spacing (m)	Working length (m/h)	Average speed	Production factor
				Hectares
GTA 10	1,53	7.000	0,90	0,96
GTA 12	1,87	7.000	0,90	1,17
GTA 14	2,39	7.000	0,90	1,50
GTA 16	2,55	7.000	0,90	1,60
GTA 18	2,89	7.000	0,90	1,82
GTA 20	3,23	7.000	0,90	2,03

01 - The formula to calculate the appropriate production refers to the calculation of the area to be worked by the disc harrow. If you want to know how long it will take to work an area of known value, simply divide the value of this area by the hourly production of the disc harrow.

- **Example:** How long (x) it will take for a 14-disc disc harrow to produce 35 hectares at an average speed of 7km / h?

$$X = \frac{35 \text{ Ha}}{1.70 \text{ Ha / h}} = 20,5 \text{ hours approx.}$$

02 - The hourly production can vary by factors that alter the pace of work, for example: humidity and soil hardness, land slope and inadequate adjustments. These factors are different from those in the Table above, which shows field work in soils under normal conditions.

13. IDENTIFICATION

- In order to refer parts catalogues or apply technical support from Baldan, always indicate model (1), serial number (2), manufacture date (3) located on the identification tag.

ALWAYS REQUIRE BALDAN ORIGINAL PARTS

 BALDAN BALDAN IMPLEMENTOS AGRÍCOLAS S/A. AV. BALDAN, 1500 NOVA MATÃO CEP 15.993-900 MATÃO-SP BRASIL FONE: (16) 3221-8500 CNPJ: 52.311.347/0009-06 CREA/SP 0170977		
01 — Modelo / Model	Date / Date — 03	
02 — N° de Série / Serial Number	Tipo / Type	
Capacidade / Load Capacity	Peso / Weight	



PUBLICATIONS

Code: 6055010029-3
CPT: GTA13319A



WARNING

The drawings in this instructions manual are for illustrative purposes only. To enable a better overview and detailed instructions, on some drawings in this manual, safety devices (covers, shields, etc..) were removed. Never operate the agricultural wagon without these devices.



CONTACT

*If you have questions, never operate the GTA see the post sale.
Phone: 0800-152577
e-mail: posvenda@baldan.com.br*

PRODUCT IDENTIFICATION

- Do the identification below to always have the properly informations about your equipment life time.

Owner: _____

Dealer: _____

Farm: _____

City: _____ Country: _____

Model: _____

Warranty certified number: _____

Serial number: _____

Purchase date: _____ / _____ / _____

NOTE:

Opis. Nr: _____

CERTIFICATE OF WARRANTY

- 01 - **BALDAN IMPLEMENTOS AGRÍCOLAS S/A**, guarantee the normal operation of the product for a 6 (six) months period dated from the dealers's bill of sale to the first final customer.
- 02 - During this period, **Baldan** compromise itself to repair the material or manufacturing defects, but the labour, the freight and other expenses are the dealer's responsibility.
- 03 - At the guarantee period, all the request and replacement of any defective part must be made to the dealer of the region, which will send the defective part for analysis at **Baldan**.
- 04 - When this procedure won't be possible and the dealer couldn't have the ability to solve the problem, the dealer can ask for **Baldan's Technical Assistance** using the specific form delivered to them.
- 05 - After the analysis of the items replaced by **Baldan Technical Assistance** and if we conclude that it wasn't a guarantee problem, then the dealer will be the responsible for all costs related to the replacement; as well as material expenses, travel including accommodation and meals, also the accessories, lubricant used or any other expenses after having called the Technical Assistance. And, withal, the company Baldan is authorized to issue the billing in name of the respective reseller.
- 06 - Any repair made to the product which is in warranty period by the dealer, will only be authorized by Baldan after budget previous presentation describing pieces and labour to be accomplished.
- 07 - It is out of this term the product which has repairs or modifications not made by dealers from Baldan's network, as well as pieces applications or not authentic components to the product by the user.
- 08 - This certificate of guarantee will become invalid when notice that the damage or defect is the result of incorrect use of the product, of instructions non-observance or operator's inexperience.

- 09 - It's stipulated that this guarantee don't cover tires, polyethylene deposits, universal joints, hydraulic components, etc, wich equipments are guarantee by their manufacturers.
- 10 - The material or manufacture defects, object of this certificate of guarantee, will not be, by any hypotesis, reason for cancellation of the contract of sale, or indemnity of any kind.
- 11 - For a warranty solicitation to the distributor, you have to proceed in the following manner:
- 12 - Send the technical informe detailed telling the problem (technical assistance request form to the client), you can find it send us an email to **after-sales@baldan.com.br** or acessing our website.
- 13 - If it's possible send films and photos from the requested spare parts.
- 14 - To point at the form: serial number, manufacture year, etc, that is, all information asked at the form. The damage spare parts should be available for analysis of the the after sales department in a future visit (in case of requested).
- 15 - **Baldan** keeps the right of changing and or improve the technical characteristics of its products, without notice and without the obligation of act like this way with its previously manufactured products.

INSPECTION AND DELIVERY CERTIFICATE

- **SERVICE BEFORE THE DELIVERY:** This equipment was very carefully prepared by the dealer's organization, inspected in all its parts in agreement with the manufacture's prescription.
- **DELIVERY SERVICE:** The user was informed about the current guarantee terms and instructed about maintenance care and utilization.
- I confirm that I was informed about the current guarantee terms and instructed about the correct utilization and maintenance of this product.

Product: _____ *Serial number:* _____

Date: _____ *Bill of sale:* _____ *Store:* _____

City: _____ *State:* _____ *Zip code:* _____

Owner: _____ *Phone:* _____

Adress: _____ *Number:* _____

City: _____ *State:* _____

E-mail: _____ *Date of sale:* _____

INSPECTION AND DELIVERY CERTIFICATE

- **SERVICE BEFORE THE DELIVERY:** This equipment was very carefully prepared by the dealer's organization, inspected in all its parts in agreement with the manufacture's prescription.
- **DELIVERY SERVICE:** The user was informed about the current guarantee terms and instructed about maintenance care and utilization.
- I confirm that I was informed about the current guarantee terms and instructed about the correct utilization and maintenance of this product.

Product: _____ *Serial number:* _____

Date: _____ *Bill of sale:* _____ *Store:* _____

City: _____ *State:* _____ *Zip code:* _____

Owner: _____ *Phone:* _____

Adress: _____ *Number:* _____

City: _____ *State:* _____

E-mail: _____ *Date of sale:* _____

INSPECTION AND DELIVERY CERTIFICATE

- **SERVICE BEFORE THE DELIVERY:** This equipment was very carefully prepared by the dealer's organization, inspected in all its parts in agreement with the manufacture's prescription.
- **DELIVERY SERVICE:** The user was informed about the current guarantee terms and instructed about maintenance care and utilization.
- I confirm that I was informed about the current guarantee terms and instructed about the correct utilization and maintenance of this product.

Product: _____ Serial number: _____

Date: _____ Bill of sale: _____ Store: _____

City: _____ State: _____ Zip code: _____

Owner: _____ Phone: _____

Address: _____ Number: _____

City: _____ State: _____

E-mail: _____ Date of sale: _____

3ª Page - Manufacturer

Please send this filled copy to Baldan, until 15 days after the purchase.

Signature / Store's stamp _____



Avenida Baldan, 1500
Nova Matão
15.993-900
Matão/SP - Brasil
sac@baldan.com.br
export@baldan.com.br

+55 16 3221 6500
baldan.com.br